



# Safety Data Sheet

## Spartan Chemical Company, Inc.

Revision Date: 23-Sep-2016

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Identifier**

**Product Name:** CLEAN ON THE GO AIRLIFT TROPICAL [13]  
**Product Number:** 4710  
**Recommended Use:** Air freshener  
**Uses Advised Against:** For Industrial and Institutional Use Only

**Manufacturer/Supplier:** Spartan Chemical Company, Inc.  
1110 Spartan Drive  
Maumee, Ohio 43537 USA  
800-537-8990 (Business hours)  
[www.spartanchemical.com](http://www.spartanchemical.com)

**24 Hour Emergency Phone Numbers:**

**Medical Emergency/Information:** 888-314-6171  
**Transportation/Spill/Leak:** CHEMTREC 800-424-9300

### 2. HAZARDS IDENTIFICATION

**GHS Classification**

Skin Corrosion/Irritation: Category 2  
Serious Eye Damage/Eye Irritation: Category 1  
Flammable Liquids: Category 3

**GHS Label Elements**

**Signal Word:**

**Danger**

**Symbols:**



**Hazard Statements:**

Causes skin irritation.  
Causes serious eye damage  
Flammable liquid and vapor.

**Precautionary Statements:**

**Prevention:**

Wash hands and any exposed skin thoroughly after handling.  
Wear eye / face protection  
Wear protective gloves  
Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
Keep container tightly closed  
Ground container and receiving equipment.  
Use explosion-proof electrical equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge

**Response:**

**-Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

**-Skin**

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse

<b>-Specific Treatment:</b>	See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.
<b>Fire:</b>	In case of fire: Use CO2, dry chemical, or foam for extinction
<b>Storage:</b>	Store in a well-ventilated place. Keep cool
<b>Disposal:</b>	Dispose of contents and container in accordance with local, state and federal regulations.
<b>Hazards Not Otherwise Classified:</b>	Not Applicable
<b>Other Information:</b>	<ul style="list-style-type: none"> <li>• May be harmful if swallowed.</li> <li>• Keep out of reach of children.</li> </ul>

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
water	7732-18-5	30-60
alcohol ethoxylate	68439-46-3	10-30
isopropanol	67-63-0	5-10
alcohol ethoxylate	68131-40-8	3-7
alkyl dimethyl benzyl ammonium chloride	68424-85-1	1-5
hexylene glycol	107-41-5	1-5
fragrance	PROPRIETARY	1-5
methylidihydrojasmonate	24851-98-7	1-5

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

<b>-Eye Contact:</b>	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.
<b>-Skin Contact:</b>	Wash with plenty of soap and water Take off contaminated clothing and wash before reuse If skin irritation occurs: Get medical attention.
<b>-Inhalation:</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison control center or physician if you feel unwell.
<b>-Ingestion:</b>	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention if you feel unwell.
<b>Note to Physicians:</b>	Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

<b>Suitable Extinguishing Media:</b>	Water spray (fog), Carbon dioxide, Foam, Dry chemical, Water
<b>Specific Hazards Arising from the Chemical:</b>	Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Combustion products are toxic.
<b>Hazardous Combustion Products:</b>	May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.
<b>Protective Equipment and Precautions for Firefighters:</b>	Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear. Cool fire-exposed containers with water spray.

### 6. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions:</b>	Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
<b>Environmental Precautions:</b>	Do not rinse spill onto the ground, into storm sewers or bodies of water.
<b>Methods for Clean-Up:</b>	Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

## 7. HANDLING AND STORAGE

**Advice on Safe Handling:** Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling. Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

**Storage Conditions:** Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep container tightly closed in a dry and well-ventilated place.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Occupational Exposure Limits:

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
isopropanol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m <sup>3</sup> (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>
hexylene glycol 107-41-5	Ceiling: 25 ppm	(vacated) Ceiling: 25 ppm (vacated) Ceiling: 125 mg/m <sup>3</sup>	Ceiling: 25 ppm Ceiling: 125 mg/m <sup>3</sup>

**Engineering Controls:** Provide good general ventilation.  
If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other engineering controls should be considered.

### Personal Protective Equipment

**Eye/Face Protection:** Wear splash goggles.

**Skin and Body Protection:** Wear rubber or other chemical-resistant gloves.

**Respiratory Protection:** Not required with expected use.

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section 3 should be considered.

**General Hygiene Considerations:** Wash hands and any exposed skin thoroughly after handling.  
See 29 CFR 1910.132-138 for further guidance.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance/Physical State:</b>	Liquid
<b>Color:</b>	Pink
<b>Odor:</b>	Tropical floral fragrance
<b>pH:</b>	6.0-7.0
<b>Melting Point / Freezing Point:</b>	No information available.
<b>Boiling Point / Boiling Range:</b>	93 °C / 199 °F
<b>Flash Point:</b>	41 °C / 106 °F ASTM D56
<b>Evaporation Rate:</b>	< 1 (Butyl acetate = 1)
<b>Flammability (solid, gas)</b>	No information available.
<b>Upper Flammability Limit:</b>	No information available.
<b>Lower Flammability Limit:</b>	No information available.
<b>Vapor Pressure:</b>	No information available.
<b>Vapor Density:</b>	No information available.
<b>Specific Gravity:</b>	0.99
<b>Solubility(ies):</b>	Soluble in water
<b>Partition Coefficient:</b>	No information available.
<b>Autoignition Temperature:</b>	No information available.
<b>Decomposition Temperature:</b>	No information available.
<b>Viscosity:</b>	No information available.

## 10. STABILITY AND REACTIVITY

**Reactivity:** This material is considered to be non-reactive under normal conditions of use.

**Chemical Stability:** Stable under normal conditions.

**Possibility of Hazardous Reactions:** Not expected to occur with normal handling and storage.  
**Conditions to Avoid:** Extremes of temperature and direct sunlight. Heat, flames and sparks.  
**Incompatible Materials:** Strong oxidizing agents. Strong acids.  
**Hazardous Decomposition Products:** May include carbon monoxide, carbon dioxide (CO<sub>2</sub>) and other toxic gases or vapors.

## 11. TOXICOLOGICAL INFORMATION

**Likely Routes of Exposure:** Eyes, Skin, Ingestion, Inhalation.  
**Symptoms of Exposure:**  
**-Eye Contact:** Pain, redness, swelling of the conjunctiva and tissue damage. Eye contact may cause permanent damage.  
**-Skin Contact:** Pain, redness and cracking of the skin.  
**-Inhalation:** Nasal discomfort and coughing.  
**-Ingestion:** Pain, nausea, vomiting and diarrhea. Ingestion may cause irritation to mucous membranes.  
**Immediate, Delayed, Chronic Effects**  
**Product Information:** Data not available or insufficient for classification.  
**Target Organ Effects:** -Eyes. Respiratory System. -Skin. Central nervous system.

### Numerical Measures of Toxicity

The following acute toxicity estimates (ATE) are calculated based on the GHS document.

ATEmix (oral): 2367 mg/kg  
 ATEmix (dermal): 4921 mg/kg  
 ATEmix (inhalation-dust/mist): 19.7 mg/l  
 ATEmix (inhalation-vapor): 79 mg/l

### Component Acute Toxicity Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
water 7732-18-5	> 90 mL/kg ( Rat )	Not Available	Not Available
alcohol ethoxylate 68439-46-3	= 1378 mg/kg ( Rat )	> 2 g/kg ( Rabbit )	Not Available
isopropanol 67-63-0	= 4396 mg/kg ( Rat )	= 12800 mg/kg ( Rat ) = 12870 mg/kg ( Rabbit )	= 72.6 mg/L ( Rat ) 4 h
alcohol ethoxylate 68131-40-8	= 32 mL/kg ( Rat )	= 5660 µL/kg ( Rabbit )	Not Available
alkyl dimethyl benzyl ammonium chloride 68424-85-1	= 426 mg/kg ( Rat )	Not Available	Not Available
hexylene glycol 107-41-5	= 3692 mg/kg ( Rat )	= 8560 µL/kg ( Rabbit )	> 310 mg/m <sup>3</sup> ( Rat ) 1 h
methylhydrojasmonate 24851-98-7	> 5 g/kg ( Rat )	Not Available	Not Available

**Carcinogenicity:** No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
isopropanol 67-63-0	1000: 96 h <i>Desmodesmus subspicatus</i> mg/L EC50 1000: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	9640: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 11130: 96 h <i>Pimephales promelas</i> mg/L LC50 static 1400000: 96 h <i>Lepomis macrochirus</i> µg/L LC50	Not Available	13299: 48 h <i>Daphnia magna</i> mg/L EC50

hexylene glycol 107-41-5	Not Available	10500 - 11000: 96 h Pimephales promelas mg/L LC50 flow-through 10000: 96 h Lepomis macrochirus mg/L LC50 static 8690: 96 h Pimephales promelas mg/L LC50 flow-through 10700: 96 h Pimephales promelas mg/L LC50 static	Not Available	2700 - 3700: 48 h Daphnia magna mg/L EC50
-----------------------------	---------------	--	---------------	--

**Persistence and Degradability:** No information available.

**Bioaccumulation:** No information available.

**Other Adverse Effects:** No information available.

### 13. DISPOSAL CONSIDERATIONS

**Disposal of Wastes:** Dispose of in accordance with federal, state and local regulations.

**Contaminated Packaging:** Dispose of in accordance with federal, state and local regulations.

**US EPA Waste Number:** D001

### 14. TRANSPORT INFORMATION

**DOT:**

**UN/ID No:** UN1993

**Proper Shipping Name:** Flammable liquids, n.o.s., (Isopropanol)

**Hazard Class:** 3

**Packing Group:** III

**Special Provisions:**

Class 3, Packing Group III materials meet the exception requirements of section 49 CFR 173.150 when individual containers of not more than 1.3 gallons are packed in a strong outer packaging and ground transportation is utilized. Such containers may be reclassified as "Limited Quantity".

Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Check with a trained hazardous materials transportation expert for information specific to your situation.

**IMDG:**

**UN/ID No:** UN1993

**Proper Shipping Name:** Flammable liquids, n.o.s., (Isopropanol)

**Hazard Class:** 3

**Packing Group:** III

### 15. REGULATORY INFORMATION

**TSCA Status:** (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

**SARA 313**

This product contains the following listed substances:

**isopropanol**

CAS No 67-63-0 only if manufactured by the strong acid process, no supplier notification

**SARA 311/312 Hazard Categories**

**Acute Health Hazard:** Yes

**Chronic Health Hazard:** No

**Fire Hazard:** Yes

**Sudden release of pressure hazard:** No

**Reactive Hazard:** No

**California Proposition 65**

This product is not subject to warning requirements under California Proposition 65.

**16. OTHER INFORMATION**

<b>NFPA</b>	<b>Health Hazards: 2</b>	<b>Flammability: 2</b>	<b>Instability: 0</b>	<b>Special: N/A</b>
<b>HMIS</b>	<b>Health Hazards: 2</b>	<b>Flammability: 2</b>	<b>Physical Hazards: 0</b>	

**Revision Date:** 23-Sep-2016  
**Reasons for Revision:** Section 2, 3, and 10

**Disclaimer:**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**